



Technical Data Sheet: HP6610NT

Product manual	<p>HP6610NT is an aliphatic urethane acrylate oligomer developed for UV/EB-cured coatings and inks. HP6610NT imparts hardness, very fast cure response, and nonyellowing characteristics to these applications.</p>	
Product features	<p>Non-yellowing</p> <p>Very fast curing speed</p> <p>Good Adhesion</p> <p>Good Hardness</p> <p>Good Weatherability</p> <p>High Abrasion Resistance</p>	
Suggested application	<p>Coatings</p> <p>Coatings, plastic</p> <p>Inks, flexo</p> <p>Inks, litho</p>	
Specifications	Functional basis (theoretical)	6
	Appearance(By vision)	Little yellow liquid
	Viscosity (CPS/60℃)	1400-3600
	Color (APHA)	≤ 100
	Efficient content(%)	100
Packing	<p>Net weight 50KG plastic bucket and net weight 200KG iron drum.</p>	
Storage conditions	<p>Resin please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months.</p>	
Use matters	<p>Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.</p>	