



# Technical Data Sheet: CR91708

<b>Product manual</b>	CR91708 is a modified epoxy acrylate oligomer, which has fast curing speed, low shrinkage and good adhesion in UV/EB curing coatings, inks and adhesives. CR91708 can be used for the coating of plastic, metal and wood substrates, nail glue.	
<b>Product features</b>	Fast curing speed Good flexibility Good metal adhesion Good plastic adhesion Low shrinkage No monomer	
<b>Suggested application</b>	Nail Polish Ink Copy varnish Wood varnish	
<b>Specifications</b>	Functional basis (theoretical)	2
	Appearance(By vision)	Little yellow liquid
	Viscosity (CPS/60°C)	13000-25000
	Color (APHA)	≤ 100
	Acid Value (mgKOH/g)	<5
	Efficient content(%)	100
<b>Packing</b>	Net weight 50KG plastic bucket and net weight 200KG iron drum.	
<b>Storage conditions</b>	Please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 °C, storage conditions under normal conditions for at least 6 months.	
<b>Use matters</b>	Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.	