



## Technical Data Sheet: CR90685

<b>Product manual</b>	<b>CR90685</b> is an aliphatic polyurethane acrylate oligomer. It has excellent toughness and gloss. It can be used for anaerobic glue, structural glue, nail polish extension glue, scrubbing sealant, etc.	
<b>Product features</b>	Excellent toughness Good gloss Good solvent resistance	
<b>Suggested application</b>	Nail polish extension glue Nail polish scrubbing seal anaerobic glue structural glue	
<b>Specifications</b>	Functional basis (theoretical)	2
	Appearance(By vision)	Clear liquid
	Viscosity (CPS/60°C)	9000-19000
	Color (APHA)	≤50
	Efficient content(%)	100%
<b>Packing</b>	Net weight 50KG plastic bucket and net weight 200KG iron drum.	
<b>Storage conditions</b>	Store product indoors at temperatures greater than product's freezing point (or greater than 0C/32F if no freezing point available) and <b>below 38C/100F</b> . Avoid prolonged (longer than shelf-life) storage temperatures above 38C/100F. Store in tightly closed containers in a properly vented storage area away from: heat, sparks, open flame, strong oxidizers, radiation, and other initiators. Prevent contamination by foreign materials. Prevent moisture contact. Use only non-sparking tools and limit storage time. Unless specified elsewhere, <b>shelf-life is 6 months from receipt</b> .	
<b>Use matters</b>	Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.	