



Technical Data Sheet: **CR90886**

Product manual	CR90886 is a two-functional modified epoxy acrylate oligomer; it has good water resistance, good solvent resistance, good chemical resistance, high gloss, fast curing, and good adhesion to glass and metal.										
Product features	Good water resistance Fast curing speed High gloss										
Suggested application	Adhesive glass Adhesive metal										
Specifications	<table><tr><td>Functional basis (theoretical)</td><td>2</td></tr><tr><td>Appearance(By vision)</td><td>Clear liquid</td></tr><tr><td>Viscosity (CPS/60℃)</td><td>7000-11000</td></tr><tr><td>Color (APHA)</td><td>≤ 500</td></tr><tr><td>Efficient content(%)</td><td>≥99.9</td></tr></table>	Functional basis (theoretical)	2	Appearance(By vision)	Clear liquid	Viscosity (CPS/60℃)	7000-11000	Color (APHA)	≤ 500	Efficient content(%)	≥99.9
Functional basis (theoretical)	2										
Appearance(By vision)	Clear liquid										
Viscosity (CPS/60℃)	7000-11000										
Color (APHA)	≤ 500										
Efficient content(%)	≥99.9										
Packing	Net weight 50KG plastic bucket and net weight 200KG iron drum.										
Storage conditions	Resin please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months.										
Use matters	Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.										