



Technical Data Sheet: CR91224

Product manual	CR91224 is an aliphatic polyurethane acrylate oligomer; Its outstanding features are fast curing speed, good leveling, excellent toughness, good surface scratch resistance, good anti-fogging properties, good chemical resistance, good water resistance, and good durability. It is especially suitable for anti-fogging on the surface of substrates such as hospital goggles, glasses, bathrooms, and automobiles.	
Product features	Efficient anti-fog Good alcohol resistant Good adhesion Good chemical resistance	
Recommended use	UV anti-fog cover light UV plastic cover light	
Specifications	Functionality (theoretical)	4
	Appearance(By vision)	Clear liquid
	Viscosity (CPS/25℃)	100-300
	Color(Gardner)	≤1
	Efficient content(%)	100
Packing	Net weight 50KG plastic bucket and net weight 200KG iron drum	
Storage conditions	Please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months.	
Use matters	Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.	