



Technical Data Sheet: CR91540

Product manual	CR91540 is a tri-functional aliphatic urethane acrylate resin; it has the characteristics of fast curing speed, good toughness, yellowing resistance, high surface hardness, good scratch resistance and good stability under LED curing. It is especially suitable for various coatings such as nail polish sealant, color glue, UV dispensing, plastic finishing paint, UV wood paint and so on.	
Product features	Fast curing speed High hardness Good yellow and weather resistance Good toughness	
Recommended use	Nail polish seal UV dispensing Plastic finishing paint Wood Coatings	
Specifications	Functionality (theoretical)	3
	Appearance(By vision)	Clear liquid
	Viscosity (CPS/60℃)	3000-6000
	Color(Gardner)	≤1
	Efficient content(%)	100
Packing	Net weight 50KG plastic bucket and net weight 200KG iron drum.	
Storage conditions	Please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months.	
Use matters	Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.	