



# Technical Data Sheet: CR91568

<b>Product manual</b>	<b>CR91568</b> is a polyurethane acrylate oligomer. It has the characteristics of low viscosity, low odor, low irritation, easy matting, high hardness, good abrasion and scratch resistance, good leveling, good fullness and good toughness. It is especially suitable for PVC/SPC coatings, wood coatings, plastic coatings and other fields.	
<b>Product features</b>	Low odor and low irritation Easy to matting Good toughness Good scratch resistance	
<b>Recommended use</b>	PVC/SPC coatings Wood coatings Plastic coatings	
<b>Specifications</b>	Functional basis (theoretical)	2
	Appearance(By vision)	Clear liquid
	Viscosity (CPS/25℃)	300-800
	Color(Gardner)	≤ 2
	Efficient content(%)	100
<b>Packing</b>	Net weight 50KG plastic bucket and net weight 200KG iron drum.	
<b>Storage conditions</b>	Please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months.	
<b>Use matters</b>	Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.	