



## Technical Data Sheet: HP6203

<b>Product manual</b>	<b>HP6203</b> is an aliphatic polyurethane diacrylate oligomer. It has the characteristics of low shrinkage, good water resistance, good flexibility and good adhesion between metal layers; It is mainly suitable for PVD primer coating.	
<b>Product features</b>	Easily metalized Resistant to solvent dilution Good boiling water resistance Good flexibility Cost-effective	
<b>Recommended use</b>	Plastic coatings Vacuum plating primer	
<b>Specifications</b>	Functionality (theoretical)	2
	Appearance(By vision)	Clear liquid
	Viscosity (CPS/60℃)	40000-60000
	Color(APHA)	≤100
	Efficient content(%)	100
	Acid Value	≤1
<b>Packing</b>	Net weight 50KG plastic bucket and net weight 200KG iron drum	
<b>Storage conditions</b>	Please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months.	
<b>Use matters</b>	Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.	