



## Technical Data Sheet: HT7216

<b>Product manual</b>	<b>HT7216</b> is a polyester acrylate oligomer. It has good flexibility, fast curing speed, good yellow resistance and good leveling. <b>HT7216</b> can be used on wood coatings, plastic coatings and VM primer.	
<b>Product features</b>	<p>Fast cure speed</p> <p>Good leveling and fullness</p> <p>Good yellow resistance</p> <p>Cost-effective</p>	
<b>Recommended use</b>	<p>Wood coatings</p> <p>Plastic coatings</p> <p>VM primer</p>	
<b>Specifications</b>	Functionality (theoretical)	4
	Appearance (By vision)	Clear liquid
	Viscosity (CPS/25°C)	8000-15000
	Color (Gardner)	≤1
	Efficient content (%)	100
<b>Packing</b>	Net weight 50KG plastic bucket and net weight 200KG iron drum.	
<b>Storage conditions</b>	Please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 °C, storage conditions under normal conditions for at least 6 months.	
<b>Use matters</b>	<p>Avoid touching the skin and clothing, wear protective gloves when handling;</p> <p>Leak with a cloth when the leak, and wash with ethyl acetate;</p> <p>for details, please refer to the Material Safety Instructions (MSDS);</p> <p>Each batch of goods to be tested before they can be put into production.</p>	