



Technical Data Sheet: HP6226NT

Product manual	HP6226NT is an aliphatic urethane acrylate oligomer. HP6226NT was developed for UV curable coating and ink applications, where adhesion and weathering resistance are required. HP6226NT demonstrates excellent weathering properties.	
Product features	Abrasion Resistance Adhesion Chemical Resistance Flexibility Heat Resistance Impact Strength Low Shrinkage Water Resistance Weatherability Fast cure speed	
Suggested application	Coatings Coatings, floor Coatings, metal Coatings, paper Inks	
Specifications	Functional basis (theoretical)	2
	Appearance(By vision)	Little yellow liquid
	Viscosity(CPS/60℃)	18000-62000
	Color (APHA)	≤ 100
	Efficient content(%)	100
Packing	Net weight 50KG plastic bucket and net weight 200KG iron drum	
Storage conditions	Resin please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months.	
Use matters	Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.	