



Technical Data Sheet: HP6919NT

Product manual	<p>HP6919NT is an aliphatic urethane acrylate oligomer developed for UV/EB-cured coatings and inks. HP6919NT imparts hardness & toughness, very fast cure response, and nonyellowing characteristics to these applications.</p>	
Product features	<p>Non-yellowing Very fast cure Good Adhesion Good Hardness & toughness Good Weatherability High Abrasion Resistance Vibration resistance</p>	
Suggested application	<p>Coatings Coatings, plastic Inks, flexo Inks, litho</p>	
Specifications	Functional basis (theoretical)	9
	Appearance(By vision)	Little yellow liquid
	Viscosity (CPS/60℃)	6000-14000
	Color (APHA)	≤ 100
	Efficient content(%)	100
Packing	<p>Net weight 50KG plastic bucket and net weight 200KG iron drum.</p>	
Storage conditions	<p>Resin please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months.</p>	
Use matters	<p>Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.</p>	